



## The MS2-22 / MS1-40 Single Level Vehicle



**MS2-22 DC Powered Unit**  
(10K Option & Extended Yoke Shown)



**Enclosed Operators Platform & Free Flowing Roller Bed**  
(10K Option & Extended Yoke Shown)

### Dimensional Specifications

(Specifications Subject to Change without Notice)

Overall Width:	63.00"
Overall Length:	100.50"
Battery Compartment Width:	(1) 44.00" or (2) @ 22.00"
Lowered Roller Bed Height:	6.50" A1 / 5.50" A2
Elevated Roller Bed Height:	23.50 A1 / 22.50 A2
Vehicle Weight:	2500 Lbs. or 1136 Kgs.

### Performance Specifications

(Specifications Subject to Change without Notice)

Capacity:	6000 Lbs. or 2727 Kgs.
Travel Speed:	127 ft. / Minute
Lift Cycle Time:	10.50 ft. / Minute
Bridge Traverse Speed:	6 Seconds
Hydraulic System Pressure:	1900 PSI (Sub-System Pressures Vary)
Input / Operating Voltage:	2 HP VDC, 2000 RPM Motor 12-85-9 Battery Suggested Fitting (480 / 575 VAC Options Available, Consult Factory)
Control Circuit Voltage:	24 Volt DC (Safer for Operator)