



The MS2-40* Single Level Vehicle



MS2-40-10K Unit
(Optional 10K/ AC Powered Vehicle w/Standard Yoke Shown)



Optional AC Power Pack
(Std 480 VAC, 575 VAC Available, Consult Factory)

Dimensional Specifications

(Specifications Subject to Change without Notice)

Overall Width:	63.00"
Overall Length:	131"
Battery Compartment Width:	(2) 40.00"
Lowered Roller Bed Height:	6.50" A1 / 5.50" A2
Elevated Roller Bed Height:	23.50 A1 / 22.50 A2
Vehicle Weight:	2800 Lbs. or 1273 Kgs.

Performance Specifications

(Specifications Subject to Change without Notice)

Capacity:	8000 Lbs. or 3636 Kgs.
Travel Speed:	127 ft. / Minute
Lift Cycle Time:	10.50 ft. / Minute
Bridge Traverse Speed:	6 Seconds
Hydraulic System Pressure:	1900 PSI (Sub-System Pressures Vary)
Input / Operating Voltage:	2 HP VDC, 2000 RPM Motor 12-85-9 Battery Suggested Fitting (480 / 575 VAC Options Available, Consult Factory)
Control Circuit Voltage:	24 Volt DC (Safer for Operator)